

Model Name : OT 40W 40-1000-ML
Model No. : 040C1000V0W
Description : Constant Current LED Driver (Isolated)
BIS Approbations : IS 15885 (Part 2 / Sec 13)
BIS Status : In Process



Technical Specifications:

Category	Parameters	Specifications
Features	Output Type Dimming Type IP Grade Insulation Class Application	Constant Current Non Dimmable IP 66 Class II Outdoor
Input	Rated Input Voltage Operating Input Voltage Frequency Input Current Input Power Power Factor ATHD No Load / Standby Power Galvanic Isolation (Input to Output) Input Overvoltage Protection Input Under voltage Protection	220 - 240VAC 160-265VAC 50-60Hz 0.201A 46W >0.95 <10% <0.5W 2.5KV >330VAC ±10VAC <80VAC ±5VAC
Output	Output Current Output Voltage Output Power Current Tolerance Efficiency Current Ripple Overload Protection Open Circuit Protection Short Circuit Protection	1000mA 28-40VDC 40W <5% ≥87% @ 100% load (240VAC) <30% Yes Yes Yes
Environment & Protection	Ambient Operating temperature Range Storage Temperature Max Case Temperature Surge Protection 440VAC Protection	0°C - 50°C -20°C to +85°C 85°C 4KV 4Hrs
Construction	Connection PRI Wire Preparation SEC Wire Preparation Dimensions Weight	Connector 2pole 45° push-in with release key 8.5-9.5mm Strip length (0.5-1.5sqmm) 8.5-9.5mm Strip length (0.5-1.5sqmm) 106x43x34MM 215Gms

Wiring instructions:

- All connections must be kept as short as possible to ensure good EMI behavior
- Mains leads should be kept apart from LED Driver and other leads (ideally 5 . 10 cm distance)
- Advice the maximum length of output wires is 2Mtrs.
- Incorrect wiring can damage LED modules.
- The wiring must be protected against short circuits to earth (sharp edged metals parts, metal cable clips,louwer, etc.)

Reach us at:  www.oasisteck.com /  mkt@oasisteck.com /  +9120 41290768 /  +91 7559441929

** The information provided herein is subject to change without notice. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Oasis.*